



SIZE	A (MM)	B (MM)
1"	223.00	290.00
1.5"	165.00	280.00
2"	222.00	300.00
2.5"	370.00	367.00
3"	290.00	367.00
4"	540.00	360.00
6"	473.00	550.00

Zenith pump protection strainers are designed to assist in removing potentially damaging material entering pumps. These are also used in process pipelines in confined spaces.

Special Features:

- Strainer Body: Manufactured from 316L stainless steel.
- Strainer Element: Manufactured from 316L Stainless Steel. Available elements include Perforated and Wedge wire.
- Easy to assemble/disassemble for ease of cleaning.
- A metal to metal seating arrangement eliminates potential leakage problems
- Wedgewire elements can also be used.

Technical Information:

Diameters: Available from 1" – 6" OD.

Materials: All wetted parts are manufactured from 316/316L Stainless Steel. Other parts 304.

Specification: US3A, Weld, RJT, DIN, SMS, ISO, IDF.

Strainer Ends: Clamp, Weld, Male, Female, Threaded.

Max Working Pressure: 10 bar Max.

Temperature: - 10 ° C to + 120 ° C (dependent on seal material)

Seal Material: EPDM, Silicone, Viton, PTFE. Other materials available on request.

Surface Finish: Brushed Polish ID/OD, Ra <0.8 µm, Glass bead blast, Mirror Polish, Electro polish.