



# WELDED AUSTENITIC STAINLESS TUBE ASTM A249/A269/A270/EN10357, JIS G3463, DIN17457, DIN11850 GB/T 24593, AS 1528.1

Thickness		0.60	0.80	1.00	1.20	1.24	1.50	1.65	2.00
Outside Diameter									
(INCH)	(MM)					18GA		16GA	
3/8	9.53	○	◇	◇	◇	◇	◇		
1/2	12.7	○	◇	◇	◇	◇	◇		
3/4	15.90		*	*	*	*	*		
3/4	19.00/19.05		*	*	*	*	*		
7/8	22.20/22.00		*	*	*	*	*		
	23.00		*	*	*	*	*		
1	25.40/25.00		*	*	*	*	*		
	28.00/28.60		*	*	*	*	*		
	29.00		*	*	*	*	*		
1 1/4	31.80/32.00		*	*	*	*	*		
	33.00		*	*	*	*	*		
	34.00		*	*	*	*	*		
	35.00		*	*	*	*	*		
1 1/2	38.10/38.00		*	*	*	*	*		
	40.00		*	*	*	*	*		
	41.00		*	*	*	*	*		
1 3/4	44.50/45.00		*	*	*	*	*		
2	50.80/51.00			*	*	*	*	*	*
	52.00			*	*	*	*	*	*
	53.00			*	*	*	*	*	*
2 1/2	63.50				*	*	*	*	*
	70.00				*	*	*	*	*

3	76.20				*	*	*	*	*
	84.00/85.00						*	*	*
3 1/2	88.90						*	*	*
4	101.60/102.00						*	*	*
	103.00/104.00						◇	◇	◇
	105.00						◇	◇	◇
	108.00						◇	◇	◇
	114.30						*	*	*
	129.00						◇	◇	◇
	154.00						◇	◇	◇
	204.00						□	□	◇

**Remark**

- Shaded Areas are within Production Range  
 - The Other Outside Diameter and Wall Thickness Subject To The Approval Of Vendor And Purchaser.  
 (O ): No Inside Polish and No Bead Remove    (◇): Bead Remove and No Inside Polish    (\*): Inside Polish and Bead Remove