

Nominal Diameter	Outside Diameter	Nominal Wall Thickness (MM)				
		ASME B36.19M				
NPS	MM	SCH-10S	SCH-40S	SCH-80S	SCH-160S	XXS
1/8"	10.30	1.24	1.73	2.41	3.15	
1/4"	13.70	1.65	2.24	3.02	3.68	
3/8"	17.20	1.65	2.31	3.20	4.01	
1/2"	21.30	2.11	2.77	3.73	4.78	7.47
3/4"	26.70	2.11	2.87	3.91	5.56	7.82
1"	33.40	2.77	3.38	4.55	6.35	9.09
1 1/4"	42.20	2.77	3.56	4.85	6.35	9.70
1 1/2"	48.30	2.77	3.68	5.08	7.14	10.15
2"	60.30	2.77	3.91	5.54	8.74	11.07
2 1/2"	73.00	3.05	5.16	7.01	9.53	14.02
3"	88.90	3.05	5.49	7.62	11.13	15.24
3 1/2"	101.60	3.05	5.74	8.08	-	16.15
4"	114.30	3.05	6.02	8.56	13.49	17.12
5"	141.30	3.40	6.55	9.53	15.88	19.05
6"	168.30	3.40	7.11	10.97	18.26	21.95
8"	219.10	3.76	8.18	12.70	23.01	22.23
Remark	- Shaded Areas are within Production Range - The Other Normal Outside Diameter and Wall Thickness Subject To The Approval Of Vendor And Purchaser.					